

5300 Beethoven Street, Los Angeles, CA 90066 TEL: (310)306-5556 • FAX: (310)821-7413 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 4043

2 - 30 MHz 1000 WATTS LINEAR POWER RF AMPLIFIER

Solid State Band-specific High Power RF Amplifier

The 4043 is a 1000 Watt band-specific amplifier that covers the 2 – 30 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 4043 comes with an extended multiyear warranty.

CIE	201	HT.	DD	$^{-1}$	OT		NIC
CIF	くしし	JII	PK	U	ا ا ک	U	ИÐ

- ♦ Thermal Overload
- ♦ Over Current
- ♦ Over Voltage

ORDERING MODELS

- ♦ R Rear Panel Connectors
- ◊ F Front Panel Connectors
- ♦ RE R model w/Control Option
- ♦ FE F model w/Control Option
- ♦ RT RE model w/Ethernet Interface
- ♦ FT FE model w/Ethernet Interface

	<u>Parameter</u>	Specification @ 25 °C		
<u>Electrical</u>				
1	Frequency Range	2 – 30 MHz		
2	Saturated Output Power	1000 Watts typical		
3	Power Output @ 1dB Comp.	600 Watts min		
5	Small Signal Gain	+60 dB min		
6	Small Signal Gain Flatness	± 2.0 dB max		
7	IP ₃	+64 dBm typical		
8	Input VSWR	2:1 max		
9	Harmonics	-15 dBc typical @ 600 Watts		
10	Spurious Signals	> -60 dBc typical @ 600 Watts		
11	Input/Output Impedance	50 Ohms nominal		
12	AC Input Power	3000 Watts max		
13	AC Input	208 ± 10% VAC, single phase		
14	RF Input	0 dBm max.		
15	RF Input Signal Format	CW/AM/FM/PM/Pulse		
16	Class of Operation	AB		
<u>Mechanical</u>				
17	Dimensions	19" x 8.75" x 20"		
18	Weight	85 lb. max		
19	Connectors	Type-N		
20	Grounding	Chassis		
21	Cooling	Internal Forced Air		
<u>Environmental</u>				
22	Operating Temperature	0° C to +50° C		
23	Operating Humidity	95% Non-condensing		
24	Operating Altitude	Up to 10,000' Above Sea Level		
25	Shock and Vibration	Normal Truck Transport		

Specifications subject to change without notice



FE Model Shown

Approved By:	Date:
Approved by.	Date.